

19" 22U TEMPEST RACK

EMI1922-TC

Feature Highlights:

NATO SDIP 27/2 Level C and EU IASG 7-03 Level C compliant

Reliable electromagnetic attenuation from 100MHz to 10GHz

Highly customizable upon request



Solution / Benefits:

The **EMI1922-TC** TEMPEST rack provides a high level of electromagnetic attenuation in order to allow the use of normal equipment in TEMPEST applications.

The rack is a Faraday cage with a solid metallic structure having front and back doors and regular 19-inch equipment mounting frame, optionally customized upon request with various configurations of power-line filters, ventilation honeycombs, pass-through waveguides for fiber optic cables, connection panels with different types of connectors and signal filters, castor wheels etc.

We can provide laboratory measurement for TEMPEST compliance of the rack fully equipped with the customer system configuration according to **NATO SDIP-27/2 Level C** or **EUIASG7-03 Level C** or we can qualify it for a requested level of electromagnetic attenuation according to the customer requirements.



EMI
SHIELDING



TECHNICAL PARAMETERS

EMI1922-TC

Brand	BST pangolin®	
Product specifications		
Product description	Static 19" 22U rack	
Interfaces	Optional	
Standard connectivity	FO	
FO passthrough waveguide	Yes	
KVM switch	Optional	
Air ventilation	Aluminum Honeycomb	
<hr/>		
Solid welded frame	Yes	
Front and rear doors	Yes	
External height	1120 mm (without caster weels) 1275 mm (with caster weels)	
External depth	1000mm	
External width	800mm	
Internal depth	930mm	
Internal width (wall to wall)	794mm	
Weight	165Kg	
Static load capacity	350Kg	
<hr/>		
Operating voltage range	90V ÷ 264V	
Operating line frequency range	47Hz ÷ 63Hz	
Max. current of power supply	40A	
Uninterruptible Power Supply	Optional	
Power distribution and circuit protection	Optional	
Management systems	Optional	
Operating ambient temperature	0 ÷ 45°C	
Operating relative humidity	0 ÷ 95% (relative humidity)	
<hr/>		
Warranty	2 Years	
<hr/>		
TEMPEST (equipped with customer system)	NATO SDIP 27/2 Level C or EU IASG 7-03 Level C	

RoHS Compliant

Provided with:

- Front door, opening protection system, fitted with key
- Power supply filter - 60 dB filter , 6kW
- Vertical organizers included
- Ventilation unit with automatic control, PDU unit with 8 Shuko sockets
- Rack grounding kit
- Floor mounting kit

Protection Rating IP20

NOTE: EMI Shielding S.R.L. has the policy of continuing development and reserves the right to make design changes and improvements to the products. Specifications are subject to be changed without notice.

Company: EMI SHIELDING S.R.L. Unique Registration Code: RO1285077, Trade Register Number: J23/503/29.01.2001 Adress : Șos. Alexandriei, No. 82, Bragadiru, Ilfov, Romania, 077025, Email: office@roshielding.ro, Certified:ISO 9001

EMI
SHIELDING

